

CASE STUDY Crown Realty Partner: Pearson Corporate Center



rown Realty Partners: Pearson Corporate
Center is a 300,000 square foot complex in
Toronto consisting of two eight-storey office towers
joined together by a central atrium. In 2018 the
building owners asked Armstrong to upgrade the
original pumps to new Design Envelope pumps.

Armstrong replaced 6 constant speed pumps with new Design Envelope variable-speed pumps. Based on modelling calculations, the new system was expected to produce energy savings of 64%. Actual energy savings are over 80%.



FACILITY TYPELarge Office



Toronto, Canada



SIZE 300,000 ft²

SITE CHALLENGES

 Mechanical Room space - pumps located on Mezzanine floor with narrow access





Complex

ANNUAL ENERGY COST

BEFORE

AFTER

\$140,072**\$18,380**

CAD

CAD

AVERAGE

AVERAGE

ANNUAL COST SAVINGS

\$121,692



CO₂ EMISSIONS

BEFORE

AFTER

150,847

1

kg co2

ka.co

AVERAGE

AVERAGE

ANNUAL CO₂
EMISSION REDUCTION

131,053

kg CO₂

TO GET YOUR ENERGY UPGRADE PROJECT STARTED, CALL:



ANNUAL **ENERGY SAVINGS** ANNUAL kWh

TOTAL kWh before TOTAL kWh after

6 chilled water pumps

1,077,480

141,386

KEY OUTCOMES:

- ✓ Energy savings of over 80% compared to the original constant speed pumps
- √ Improved occupant comfort
- ✓ Pump Manager notification identified deadhead condition
- ✓ Easy access to pump operating data showing flow, head, power usage and rpm
- ✓ Constant data-logging and performance monitoring

- Equipment 3 × Design Envelope 4300 pumps, 15hp

 - included 3 × Design Envelope 4300 pumps, 30hp
 - Pump Management Subscription

Site 300,000 ft² office complex specification







Armstrong maps each individual pump's hydraulic, motor and inverter variations at the factory, to achieve exceptional accuracy throughout the flow range. With this calibration, Armstrong Design Envelope pumps also serve as flow meters, providing reliable system flow data (+/- 5%). The testing ensures optimal performance efficiency at start-up, and Armstrong's Pump Manager helps maintain and extend efficiency throughout the pump's operating life.

